

PISONES



KPT-2L

Taco Ø 49 / 52 mm

KPT-4

Taco Ø 59 / 67 mm

KPT-5

Taco Ø 68 mm

KPT-6

Taco Ø 127 mm

KPT-1

Taco Ø 40 mm

KPT-2

Taco Ø 49 / 52 mm

Modelo	Ø taco (mm)	Ø Pistón (mm)	Carrera (mm)	Golpes por minuto	Consumo (L/min)	Peso (Kg)	Pot. / Pres sonora (dBA)	Máx vibr. (m/s ²)	Longitud (mm)	Entrada de aire	Uso
KPT-1	40	18	50	1.800	400	2,0	105 / 92	46,8	340	3/8	Q Q
KPT-2	49 / 52	22	65	1.000	500	3,0	105 / 92	58,9	460	3/8	Q Q
KPT-2L	49 / 52	22	65	1.000	500	4,0	105 / 92	51,9	1.050	3/8	Q Q
KPT-4	59 / 67	25,4	100	800	700	8,0	107 / 94	55,8	1.165	1/2	Q Q
KPT-5	68	32	127	700	850	10,0	109 / 96	54,3	1.245	1/2	Q Q
KPT-6	127	38	152	600	900	14,0	109 / 96	54,3	1.330	1/2	Q Q



TACOS PARA PISONES

KPT-1

AC-KPT1TG

Ø taco goma: 40 mm

AC-KPT1TM

Ø taco metálico: 40 mm

KPT-2 / KPT-2L

AC-KPT2TG

Ø taco goma: 52 mm

AC-KPT2TM

Ø taco metálico: 49 mm

KPT-4

AC-KPT4TG

Ø taco goma: 67 mm

AC-KPT4TM

Ø taco metálico: 59 mm

KPT-5

AC-KPT5TG

Ø taco goma: 68 mm

AC-KPT5TM

Ø taco metálico: 68 mm

KPT-6

AC-KPT6TM

Ø taco metálico: 127 mm